

24BYJ48

★重量: 40克
典型应用领域:
 家用电器
 • 空调
 • 冰箱
 • 智能洁具
 • 自动门锁
 监控器
 电子仪表

★Weight: 40g
Typical Applications:
 Home Appliances
 • Air-conditioning
 • Refrigerator
 • Intelligent Sanitary
 • Automatic Door Lock
 CCTV Monitor
 Electronic Instruments



性能参数 Performance Parameters

型号 Model	电压 Rated Voltage (DCV)	电阻 Resistance Ω/Phase (at 25°C)	频率 Operation Frequency (PPS)	牵入转矩 Pull-in Torque (mN.m)	自定位转矩 Detent Torque (mN.m)	空载牵入频率 Max. Freeload Pull-in Frequency (PPS)	空载牵出频率 Max. Freeload Pull-out Frequency (PPS)	温升 Temperature Rise(K)	噪音 Noise dB(A)	步距角 (1-2相) Step Angle (1-2phase)	绝缘等级 Insulation Class
24BYJ48	5	60	100	≥29.4	≥29.4	≥500	≥900	≤40	≤40	5.625°/64	A
	12	200	100	≥29.4	≥29.4	≥500	≥900	≤40	≤40		
	12	250	100	≥29.4	≥29.4	≥500	≥900	≤40	≤40		
	12	300	100	≥29.4	≥29.4	≥500	≥900	≤40	≤40		
	12	300	100	≥58.8	≥29.4	≥500	≥900	≤40	≤40		
	12	200	100	100	≥9.8	≥7.35	≥300	≥600	≤40	≤40	5.625°/16

机械尺寸 Mechanical Dimensions:mm

