

50SM25-3

★重量: 140克

典型应用领域:

阀门控制

家用电器

• 空调

★Weight: 140g

Typical Applications:

Valve Control

Home Appliances

• Air-conditioning



性能参数 Performance Parameters

型号 Model	额定电压 Rated Voltage (V)	额定频率 Rated Frequency (Hz)	转速 Speed (RPM)	电流 Input Current (mA)	功率 Input Power (W)	失速力矩 Stall Torque (N.m)	启动电压 Starting Voltage (V)	温升 Temperature Rise (K)	噪音 Noise dB(A)	绝缘等级 Insulation Class
50SM25-3	12	50/60	2	≤280	≤3	≥0.90	≤18	≤60	≤40	A
	24	50/60	2	≤150	≤3	≥0.90	≤18	≤60	≤40	
	115	50/60	2	≤35	≤3	≥0.90	≤90	≤60	≤40	
	220-240	50/60	2	≤20	≤3	≥0.90	≤180	≤60	≤40	
	12	50/60	4/3	≤280	≤3	≥1.40	≤18	≤60	≤40	
	24	50/60	4/3	≤150	≤3	≥1.40	≤18	≤60	≤40	
	115	50/60	4/3	≤35	≤3	≥1.40	≤90	≤60	≤40	
	220-240	50/60	4/3	≤20	≤3	≥1.40	≤180	≤60	≤40	
	12	50/60	12	≤280	≤3	≥0.15	≤18	≤60	≤40	
	24	50/60	12	≤150	≤3	≥0.15	≤18	≤60	≤40	
	115	50/60	12	≤35	≤3	≥0.15	≤90	≤60	≤40	
	220-240	50/60	12	≤20	≤3	≥0.15	≤180	≤60	≤40	

机械尺寸 Mechanical Dimensions:mm

