

## 50HM25

★重量：220克

典型应用领域：

阀门控制

★Weight:220g

Typical Applications:

Valve Control



### 性能参数 Performance Parameters

型号 Model	额定电压 Rated Voltage (V)	额定频率 Rated Frequency (Hz)	转速 Speed (RPM)	功率 Input Power (W)	输出力矩 Output Torque (Kgf.cm)	回复力矩 Return Torque (Kgf.cm)	启动电压 Starting Voltage (VAC)	温升 Temperature Rise(K)	噪音 Noise (dB)	绝缘等级 Insulation Class
50HM25	24	50/60	5/6	6/5	≥0.65	≤0.22	≤18	≤80	≤50	F
	24	50/60	4/4.8	6/5	≥0.8	≤0.28	≤18	≤80	≤50	
	24	50/60	3.33/4	6/5	≥1.08	≤0.32	≤18	≤80	≤50	
	24	50/60	0.83/1	6/5	≥4.32	≤1.44	≤18	≤80	≤50	
	120	50/60	5/6	6/5	≥0.65	≤0.22	≤85	≤80	≤50	
	120	50/60	4/4.8	6/5	≥0.8	≤0.28	≤85	≤80	≤50	
	120	50/60	3.33/4	6/5	≥1.08	≤0.32	≤85	≤80	≤50	
	120	50/60	0.83/1	6/5	≥4.32	≤1.44	≤85	≤80	≤50	
	220	50/60	5/6	6/5	≥0.65	≤0.22	≤180	≤80	≤50	
	220	50/60	4/4.8	6/5	≥0.8	≤0.28	≤180	≤80	≤50	
	220	50/60	3.33/4	6/5	≥1.08	≤0.32	≤180	≤80	≤50	
	220	50/60	0.83/1	6/5	≥4.32	≤1.44	≤180	≤80	≤50	

### 机械尺寸 Mechanical Dimensions:mm

